

Λ

~

C++ TEMPLATES

Problem Solving with Computers-II

C++

```
#include <iostream>
using namespace std;

int main()
{
    cout<<"Hello Facebook!"<<endl;
    return 0;
}
```

Finding the Maximum of Two Integers

- Here's a small function that you might write to find the maximum of two integers.


```
int maximum(int a, int b)
{
    if (a > b)
        return a;
    else
        return b;
}
```

Finding the Maximum of Two Points

```
point maximum(Point a, Point b)
{
    if (a > b)
        return a;
    else
        return b;
}
```

One Hundred Million Functions...

- Suppose your program uses 100,000,000 different data types, and you need a maximum function for each...



A Template Function for Maximum

- When you write a template function, you choose a data type for the function to depend upon...

```
template <class Item>
Item maximum(Item a, Item b)
{
    if (a > b)
        return a;
    else
        return b;
}
```

What are the advantages over `typedef`?

```
template <class Item>
Item maximum(Item a, Item b)
{
    if (a > b)
        return a;
    else
        return b;
}
```

```
typedef int item;
item maximum(item a, item b)
{
    if (a > b)
        return a;
    else
        return b;
}
```

BST, with templates:

```
template<typename Data>

class BSTNode {
public:
    BSTNode<Data>* left;
    BSTNode<Data>* right;
    BSTNode<Data>* parent;
    Data const data;

    BSTNode( const Data & d ) :
        data(d) {
        left = right = parent = 0;
    }

};
```

BST, with templates:

```
template<typename Data>

class BSTNode {
public:
    BSTNode<Data>* left;
    BSTNode<Data>* right;
    BSTNode<Data>* parent;
    Data const data;

    BSTNode( const Data & d ) :
        data(d) {
        left = right = parent = 0;
    }

};
```

How would you create a **BSTNode** object on the runtime stack?

- A. BSTNode n(10);
- B. BSTNode<int> n;
- C. BSTNode<int> n(10);
- D. BSTNode<int> n = new BSTNode<int>(10);
- E. More than one of these will work

{ } syntax OK too

*Docs not specify param in
Does not template param in*

BST, with templates:

```
template<typename Data>

class BSTNode {
public:
    BSTNode<Data>* left;
    BSTNode<Data>* right;
    BSTNode<Data>* parent;
    Data const data;

    BSTNode( const Data & d ) :
        data(d) {
        left = right = parent = 0;
    }

};
```

How would you create a **pointer** to
BSTNode with integer data?

- A. BSTNode* nodePtr;
- B. BSTNode<int> nodePtr;
- C. BSTNode<int>* nodePtr;

*BSTNode<int> *nodePtr;*

BST, with templates:

```
template<typename Data>

class BSTNode {
public:
    BSTNode<Data>* left;
    BSTNode<Data>* right;
    BSTNode<Data>* parent;
    Data const data;

    BSTNode( const Data & d ) :
        data(d) {
        left = right = parent = 0;
    }

};
```


Complete the line of code to create a new
BSTNode object with int data on the heap
and assign nodePtr to point to it.

BSTNode<int>* nodePtr

CHANGING GEARS: C++STL

- The C++ Standard Template Library is a very handy set of three built-in components:
 - Containers: Data structures
 - Iterators: Standard way to search containers
 - Algorithms: These are what we ultimately use to solve problems

C++ STL container classes



Working with a BST

```
template<typename Data>
class BST {

private:

    /** Pointer to the root of this BST, or 0 if the BST is
empty */
    BSTNode<Data>* root;

public:

    /** Default constructor. Initialize an empty BST. */
    BST() : root(nullptr){  }

    void insertAsLeftChild(BSTNode<Data>* parent, const Data &
item)
    {
        // Your code here
    }
}
```

Working with a BST: Insert

```
void insertAsLeftChild(BSTNode<Data>* parent, const Data &
item)
{
    // Your code here
}
```

Which line of code correctly inserts the data item into the BST as the left child of the parent parameter.

- A. parent.left = item;
- B. parent->left = item;
- C. parent->left = BSTNode(item);
- D. parent->left = new BSTNode<Data>(item);
- E. parent->left = new Data(item);

Working with a BST: Insert

```
void insertAsLeftChild(BSTNode<Data>* parent, const Data &
item)
{
    parent->left = new BSTNode<Data>(item);
}
```

Is this function complete? (i.e. does it do everything it needs to correctly insert the node?)

A. Yes. The function correctly inserts the data

B. No. There is something missing.

Need to update the
parent pointer of the new node

Working with a BST: Insert

```
void insertAsLeftChild(BSTNode<Data>* parent, const Data &
item)
{
    parent->left = new BSTNode<Data>(item);
}
```

Template classes

Using a Typedef Statement:

```
class bag
{
public:
    typedef int value_type;
    . . .
```

Using a Template Class:

```
template <class Item>
class bag
{
public:
    typedef Item value_type;
    . . .
```

Template classes: Non-member functions

bag operator +(const bag& b1, const bag& b2)...

```
template <class Item>
bag<Item> operator +(const bag<Item>& b1, const bag<Item>& b2)...
```

Template classes: Member function prototype

- Rewrite the prototype of the member function “count” using templates
Before (without templates)

```
class bag{  
public:  
    typedef std::size_t size_type;  
  
    ....  
    size_type count(const value_type& target) const;  
  
    ....  
};
```

Template classes: Member function definition

```
bag::size_type bag::count(const value_type& target) const ...
```

The function's return type is specified as `bag::size_type`. But this return type is specified before the compiler realizes that this is a `bag` member function. So we must put the keyword `typename` before `bag<Item>::size_type`. We also use `Item` instead of `value_type`:

```
template <class Item>
typename bag<Item>::size_type bag<Item>::count
(const Item & target) const ...
```

Template classes: Including the implementation

```
#include "bag4.template" // Include the implementation.
```

How to Convert a Container Class to a Template

1. The template prefix precedes each function prototype or implementation.
2. Outside the class definition, place the word <Item> with the class name, such as bag<Item>.
3. Use the name Item instead of value_type.
4. Outside of member functions and the class definition itself, add the keyword *typename* before any use of one of the class's type names. For example:

```
typename bag<Item>::size_type
```

5. The implementation file name now ends with .template (instead of .cxx), and it is included in the header by an include directive.
6. Eliminate any using directives in the implementation file. Therefore, we must then write std:: in front of any Standard Library function such as std::copy.
7. Some compilers require any default argument to be in both the prototype and the function implementation.